


Catalogue

of industrial laundry equipment





LA range - high spin, freestanding washer extractor

Type	LSC 65	LA 60	LA 75	LAC 60	LAC 75
Professional washers					
Capacity	6,5 kg	6 kg	7,5 kg	6 kg	7,5 kg
Heating	electrical	electrical	electrical	electrical	electrical
Extraction	1400 rpm	1150 rpm	1100 rpm	1150 rpm	1100 rpm
G-factor	530	390	360	390	360
Electrical connection	1×230-400V 50Hz 3×400V 50Hz	1×220-240V 50/60Hz 1×220-240V 50/60Hz	3×380-400V 50/60Hz 3×380-400V 50/60Hz	1×220-240V 50/60Hz 3×380-440V 50/60Hz	1×220-240V 50/60Hz 3×380-400V 50/60Hz
Electrical heating	3,2 kW	3-6-9 kW	3-6-9 kW	3-6-9 kW	3-6-9 kW
Net weight	73 kg	160 kg	165 kg	165 kg	175 kg
Door diameter	310 mm	284 mm	284 mm	284 mm	284 mm
Dimensions H×W×D	850×595×585	940×685×645	940×685×685	1070×685×665	1070×685×690

AF range - high spin, freestanding washer-extractors

Type	AF 65	AF 80	AF 105
Commercial washers			
Capacity	7 kg	8 kg	11 kg
Heating	electrical, steam hot water	electrical, steam hot water	electrical, steam hot water
Extraction	1165 rpm	1165 rpm	1075 rpm
G-factor	400	400	400
Electrical connection	1×220-240V 50/60Hz 3×380-415V+N 50/60Hz	1×220-240V 50/60Hz 3×380-415V+N 50/60Hz	1×220-240V 50/60Hz 3×380-415V+N 50/60Hz
Electrical heating	6-9 kW	6-9 kW	6-9-12 kW
Net weight	156 kg	185 kg	210 kg
Door diameter	330 mm	330 mm	410 mm
Dimensions H×W×D	1115×710×676	1115×710×726	1225×795×795

AF, LH range - high spin, freestanding washer-extractors

Type	AF 135	AF 180	AF 240	LH 335
Commercial washers				
Capacity	14 kg	18 kg	24 kg	33 kg
Heating	electrical, steam hot water	electrical, steam hot water	electrical, steam hot water	electrical, steam hot water
Extraction	1075 rpm	980 rpm	980 rpm	830 rpm
G-factor	400	400	400	350
Electrical connection	1×220-240V 50/60Hz 3×380-415V+N 50/60Hz	3×220-240V 50/60Hz 3×380-415V 50/60Hz	3×220-240V 50/60Hz 3×380-415V 50/60Hz	3×200-240V 50/60Hz 3×380-480V 50/60Hz
Electrical heating	9-12 kW	12-18 kW	18 kW	24 kW
Net weight	255 kg	300 kg	350 kg	1230 kg
Door diameter	410 mm	460 mm	460 mm	540 mm
Dimensions H×W×D	1225×795×911	1410×970×890	1410×970×1070	1905×1195×1330



LH range - high spin, freestanding washer-extractors

Type	LH 400	LH 550	LH800	LH1000	LH1250
Commercial washers					
	Capacity	40 kg	55 kg	80 kg	100 kg
Heating	electrical, steam hot water	electrical, steam hot water	electrical, steam hot water	steam hot water	steam hot water
Extraction	830 rpm	830 rpm	750 rpm	725 rpm	700 rpm
G-factor	350	350	350	350	350
Electrical connection	3×200-240V 50/60Hz 3×380-480V 50/60Hz	3×200-240V 50/60Hz 3×380-480V 50/60Hz	3×208-240V 50/60Hz 3×380-480V 50/60Hz	3×208-240V 50/60Hz 3×380-480V 50/60Hz	3×380-480V 3×200-240V 50/60Hz
Electrical heating	36 kW	54 kW	67,5 kW	-	-
Net weight	1560 kg	1630 kg	2640 kg	2850 kg	3115 kg
Door diameter	540 mm	540 mm	540 mm	540 mm	650 mm
Dimensions H×W×D	1905×1195×1430	1905×1195×1610	1996×1530×1797	2054×1688×1947	2077×1750×1984

LN range - normal spin, rigid mounted washer-extractors

Type	LN 60	LN 75	LN 95	LN 130
Commercial washers				
	Capacity	6 kg	7 kg	10,5 kg
Heating	electrical, steam hot water	electrical, steam hot water	electrical, steam hot water	electrical, steam hot water
Extraction	580 rpm	580 rpm	580 rpm	525 rpm
G-factor	100	100	100	100
Electrical connection	1×208-240V 50/60Hz 3×380-415V+N 50/60Hz	1×208-240V 50/60Hz 3×380-415V+N 50/60Hz	1×208-240V 50/60Hz 3×380-415V+N 50/60Hz	1×208-240V 50/60Hz 3×380-415V+N 50/60Hz
Electrical heating	6-9 kW	6-9 kW	6-9-12 kW	6-9-12 kW
Net weight	140 kg	140 kg	185 kg	195 kg
Door diameter	290 mm	290 mm	290 mm	410 mm
Dimensions H×W×D	1045×660×710	1045×660×710	1140×660×865	1225×750×820

LN range - normal spin, rigid mounted washer-extractors



Type	LN 180	LN 220	LN 270	LN 335
Commercial washers				
	Capacity	18 kg	22 kg	27 kg
Heating	electrical, steam hot water	electrical, steam hot water	electrical, steam hot water	electrical, steam hot water
Extraction	505 rpm	480 rpm	490 rpm	510 rpm
G-factor	100	90	100	133
Electrical connection	1×220-240V 50/60Hz 3×380-480V 50/60Hz	1×220-240V 50/60Hz 3×380-480V 50/60Hz	1×208-240V 50/60Hz 3×208-240V 50/60Hz	1×208-240V 50/60Hz 3×208-240V 50/60Hz
Electrical heating	12-18 kW	12-18 kW	18-24 kW	18-24 kW
Net weight	280 kg	280 kg	410 kg	710 kg
Door diameter	410 mm	410 mm	504 mm	504 mm
Dimensions H×W×D	1315×855×900	1315×855×1000	1380×870×1140	1460×1100×1140













LMA range - hygienic barrier, high spin, freestanding washer-extractors

Type	LMA 260	LMA 330	LMA 440	LMA 660
Hygienic barrier washers				
				
Capacity	26 kg	33 kg	44 kg	66 kg
Heating	electrical, steam hot water	electrical, steam hot water	electrical, steam hot water	electrical, steam hot water
Extraction	960 rpm	960 rpm	915 rpm	915 rpm
G-factor	335	335	350	350
Electrical connection	3×200-240V 50/60Hz 3×380-480V 50/60Hz	3×200-240V 50/60Hz 3×380-480V 50/60Hz	3×200-240V 50/60Hz 3×380-480V 50/60Hz	3×200-240V 50/60Hz 3×380-480V 50/60Hz
Electrical heating	24 kW	36 kW	45 kW	54 kW
Net weight	960 kg	1000 kg	1140 kg	1360 kg
Door diameter	498×325 mm	498×325 mm	498×325 mm	2×498×325 mm
Dimensions H×W×D	1600×1410×1060	1600×1560×1060	1650×1610×1170	1650×2160×1170

AFB range - hygienic barrier, high spin, freestanding washer-extractors






Type	AFB 180	AFB 240
Hygienic barrier washers		
		
Capacity	18 kg	24 kg
Heating	electrical, steam hot water	electrical, steam hot water
Extraction	940 rpm	940 rpm
G-factor	370	370
Electrical connection	3×220-240V 50/60 Hz 3×380-480V 50/60 Hz	3×220-240V 50/60 Hz 3×380-480V 50/60 Hz
Electrical heating	12/18 kW	18 kW
Net weight	370 kg	400 kg
Door diameter	376×325 mm	496×325 mm
Dimensions H×W×D	1420×850×1025	1420×970×1025

LMA range - hygienic barrier, high spin, freestanding washer-extractors

Type	LMA 700	LMA 900	LMA 1100	LMA 1400	LMA 1800
Hygienic barrier washers					
					
Capacity	70 kg	90 kg	110 kg	140 kg	180 kg
Heating	electrical, steam	electrical, steam	electrical, steam	electrical, steam	steam
Extraction	800 rpm	800 rpm	754 rpm	720 rpm	695 rpm
G-factor	360	360	350	350	350
Electrical connection	3×380-480V 50/60Hz	3×380-480V 50/60Hz	3×380-480V 50/60Hz	3×380-480V 50/60Hz	3×380-480V 50/60Hz
Electrical heating	54/72 kW	54/72 kW	72/96 kW	72/96 kW	-
Net weight	2600 kg	2810 kg	2990 kg	3550 kg	4990 kg
Door diameter	765×340 mm	765×340 mm	765×340 mm	765×440 mm	765×440 mm
Dimensions H×W×D	1805×2025×1615	1805×2275×1615	1855×2325×1615	2075×2435×1805	2165×2585×1905



LDR range - professional tumble dryers

Type	LDRM 120/ LDRMC 120	LDR 185	LDRM 185	LDRMS 185	LDRMT 185
Professional dryers					
	Capacity	7 kg	8,5 kg	8,5 kg	8,5 kg
Heating	electrical, heat pump	electrical, gas	electrical, gas	electrical	electrical, gas
Electrical connection	1×230V 50Hz 3×400V 50Hz	1×220-240V 50/60Hz 3×380-400V 50/60Hz	1×220-240V 50/60Hz 3×380-400V 50/60Hz	1×220-240V 50/60Hz 3×380-400V 50/60Hz	1×220-240V 50/60Hz 3×380-400V 50/60Hz
Electrical heating	3 kW	5-6 kW	5-6 kW	5-6 kW	5-6 kW
Net weight	39 kg	57 kg	57 kg	57 kg	57 kg
Door diameter	450 mm	523 mm	523 mm	523 mm	523 mm
Dimensions H×W×D	850×595×595	1092×683×711	1092×683×711	914×683×711	1092×683×711

LDRMC 120 - version with condense unit

LDRM 120 HP - version with heat pump heating

LDRMS 185 - version with controller on the bottom that can be stacked on the top of washer-extractor LA 60 or LA 75 (electrical heating only)

LDRMT 185 - version that can be placed next to washer-extractor LH 60 and LH 75 (the same height and timer on the front panel)

LS range - industrial tumble dryers

Type	LS 195	LS 250	LS 300	LSD 300	LSMS 13
Commercial dryers					
	Capacity	9 kg	11 kg	13 kg	2×13 kg
Heating	electrical - gas	electrical steam gas	electrical steam gas	electrical steam gas	electrical gas
Electrical connection	3×220-240V 50Hz 3×380-415V 50/60Hz	3×220-240V 50Hz 3×380-415V 50/60Hz	3×220-240V 50Hz 3×380-415V 50/60Hz	3×220-240V 50Hz 3×380-415V 50/60Hz	3×220-240V 50Hz 3×380-415V 50/60Hz
Electrical heating	9-12 kW	13,5 kW	18 kW	2×18 kW	18 kW
Net weight	170 kg	230 kg	250 kg	370 kg	185 kg
Door diameter	600 mm	600 mm	600 mm	2×600 mm	600 mm
Dimensions H×W×D	1465×795×815	1680×795×1070	1680×795×1160	2030×795×1240	1075×795×1240

LS range - industrial tumble dryers

Type	LS 350	LS 530	LS 680	LDR 1025	LDR 1425
Commercial dryers					
	Capacity	16 kg	24 kg	35 kg	55 kg
Heating	electrical steam gas	electrical steam gas	electrical steam gas	electrical steam gas	steam gas
Electrical connection	3×220-240V 50Hz 3×380-415V 50/60Hz	3×220-240V 50Hz 3×380-400V 50/60Hz	3×220-240V 50Hz 3×380-400V 50/60Hz	1×220-240V 50Hz 3×380-400V 50Hz	1×220-240V 50Hz 3×380-400V 50Hz
Electrical heating	24 kW	30/36 kW	36/48 kW	-	-
Net weight	250 kg	275 kg	305 kg	625 kg	761 kg
Door diameter	600 mm	810 mm	810 mm	700 mm	700 mm
Dimensions H×W×D	1680×795×1280	1975×965×1270	1975×965×1490	2177×1178×1725	2388×1349×1749



LR range - chest heated flatwork ironers

Type	LR 2510	LR 2512	LR 2514	LR 3016	LR 3020
Professional ironers					
Roller diameter	250 mm	250 mm	250 mm	300 mm	300 mm
Usefull roller length	1000 mm	1200 mm	1400 mm	1600 mm	2000 mm
Heating	electrical	electrical	electrical	electrical	electrical
Electrical connection	3×380-400V 50Hz	3×380-400V 50Hz	3×380-400V 50Hz	3×380-400V 50Hz	3×380-400V 50Hz
Electrical heating	5 kW	6 kW	7 kW	13,2 kW	16,8 kW
Net weight	100 kg	118 kg	126 kg	262 kg	294 kg
Dimensions H×W×D	1005×1400×420	1005×1600×420	1005×1800×420	1100×2200×500	1100×2600×500

LSR - cylinder heated drying ironers

Type	LSR 3316	LSR 3320
Commercial ironers		
Roller diameter	320 mm	320 mm
Usefull roller length	1664 mm	2080 mm
Heating	electrical gas	electrical gas
Electrical connection	3×208-240V 50/60Hz 3×380-415V+N 50/60Hz	3×208-240V 50/60Hz 3×380-415V+N 50/60Hz
Electrical heating	24,3 kW	27,9 kW
Net weight	410 kg	465 kg
Dimensions H×W×D	1110×2084×755	1110×2500×755

LSR - cylinder heated drying ironers

Type	LSR 5016	LSR 5020	LSR 5025	LSR 5032
Commercial ironers				
Roller diameter	500 mm	500 mm	500 mm	500 mm
Usefull roller length	1600 mm	2000 mm	2500 mm	3200 mm
Heating	electrical gas steam	electrical gas steam	electrical gas steam	electrical gas steam
Electrical connection	3×208-240V 50/60Hz 3×380-415V+N 50/60Hz	3×208-240V 50/60Hz 3×380-415V+N 50/60Hz	3×208-240V 50/60Hz 3×380-415V+N 50/60Hz	3×208-240V 50/60Hz 3×380-415V+N 50/60Hz
Electrical heating	33 kW	38 kW	55 kW	65 kW
Net weight	920 kg	1150 kg	1290 kg	1590 kg
Dimensions H×W×D	1232×2350×992	1232×2750×992	1232×3350×992	1232×3950×992



LSRP/LSRA - cylinder heated drying ironers with length folder

Type	LSRP/LSRA 5020	LSRP/LSRA 5025	LSRP/LSRA 5032
Commercial ironers			
Roller diameter	500 mm	500 mm	500 mm
Usefull roller length	2000 mm	2500 mm	3200 mm
Heating	electrical gas steam	electrical gas steam	electrical gas steam
Electrical connection	3×380-415V+N 50/60Hz 3×208-240V 50/60Hz	3×380-415V+N 50/60Hz 3×208-240V 50/60Hz	3×380-415V+N 50/60Hz 3×208-240V 50/60Hz
Electrical heating	38 kW	55 kW	65 kW
Net weight	1290 kg	1440 kg	1680 kg
Dimensions H×W×D	1568×2750×1185	1568×3350×1185	1568×3950×1185

LSREP - cylinder heated drying ironers with feeder and length folder

Type	LSREP 5020	LSREP 5025	LSREP 5032
Commercial ironers			
Roller diameter	500 mm	500 mm	500 mm
Usefull roller length	2000 mm	2500 mm	3200 mm
Heating	electrical gas steam	electrical gas steam	- gas steam
Electrical connection	3×380-415V+N 50/60Hz 3×208-240V 50/60Hz	3×380-415V+N 50/60Hz 3×208-240V 50/60Hz	3×380-415V+N 50/60Hz 3×208-240V 50/60Hz
Electrical heating	38 kW	72 kW	-
Net weight	1720 kg	2180 kg	2400 kg
Dimensions H×W×D	1760×2850×1320	1760×3450×1320	1760×4050×1320
Cross folder and stacker - to match with ironer LSREP			

LSR - Industrial Cylinder Heated Drying Ironers

Type	LSR 80
Commercial cylinder heated ironers	
Roller diameter	800 mm
Usefull roller length	3200 mm
Heating	electrical gas steam
Electrical connection	3×208-240V 50/60Hz 3×380-415V+N 50/60Hz
Electrical heating	75 kW
Gas heating	112-125 kW
Net weight	3000 kg
Dimensions H×W×D	1850×4250×1880



In the last few years, Lavamac has acquired a position as one of the market leaders as a manufacturer of industrial laundry equipment.

During the past couple of years, this market has known a strong evolution by which the market has moved from selling machines to offering „concepts“ and „solutions“.

Through an extended range of products connected to a strong know-how, Lavamac has taken advantage of this market tendency, through which they can be considered as one of the trendsetters as manufacturer of industrial laundry equipment.

Thanks to a team of more than 30 engineers, Lavamac is able to develop the necessary products on a pro-active basis and with lots of flexibility. This happens in close consultation with the clients.

Lavamac disposes of one of the most complete ranges in the industry.

- Normal spin washer extractors
- High spin rigid mounted washer extractors
- High spin soft mounted washer extractors
- Tumble dryers
- Rotary ironers
- Cylinder heated flatwork ironers
- Cylinder heated flatwork ironers with integrated feeders and folders

This range enables Lavamac to offer tailor made solutions to every market segment.

As leading market segments we can distinguish:

- Coin-operated shops
- Apartment buildings
- Drycleaning shops
- On premise laundries (hospitals, hotels, sportsclubs, restaurants, etc.)
- Commercial laundries
- Ships (both cargo and cruiseliners)
- Mops

All the machines are carefully tested with linen to make sure that all Lavamac products meet the highest quality standards.



AUTHORIZED LAVAMAC DISTRIBUTOR